

CAR CARE**Vinyl Conditioner KP 2**

Properties: Low viscous, solvent free protectant for vinyls, rubbers and plastics. KP 2 is well suited for car's exteriors.

Ingredient	Weight [%]	Description
1 WACKER® E 1044	25.0	Silicone fluid emulsion
2 WACKER® E 1656	10.0	Silicone fluid emulsion
3 Water	65.0	
q.s. Preservative		

Procedure: Disperse 1 and 2 into 3 one after another at room temperature.

Suppliers: 1, 2 Wacker Chemie AG

www.wacker.com

Further Information:

Product data sheets and material safety data sheets of WACKER® - products can be ordered from our WACKER-subsiidiaries or via the Internet www.wacker.com.

For further questions, please contact our WACKER® SILICONES INFO-SERVICE:

Wacker Chemie AG
WACKER SILICONES
Hanns-Seidel-Platz 4
D-81737 München

e-mail: info.silicones@wacker.com
phone: +49 89 6279-0

WACKER® is a registered trademark of Wacker Chemie AG.

The data presented in this starting formulation are in accordance with the present state of our knowledge. The information given in this starting formulation should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the product for a particular purpose.