

**CAR CARE****Wash & Wax WW 1**

**Properties:** In DIY applications WW 1 is added to the final rinse water before drying the car with a cloth. It effects a fast breakdown of the water film and forms a hydrophobic surface.

In automatic car washes WW 1 is sprayed on after the car has been washed. It effects a fast breakdown of the water film and provides excellent hydrophobicity and durability.

Application ratio: 1 : 50 to 1 : 100.

<b>Ingredient</b>	<b>Weight [%]</b>	<b>Description</b>
1 WACKER® E 1656	8.3	Silicone fluid emulsion
2 WACKER® E 32	14.3	Silicone wax emulsion
3 Water	77.4	
q.s. Preservative		

**Procedure:** Disperse 1 and 2 into 3 one after another at room temperature.

**Suppliers:** 1, 2 Wacker Chemie AG [www.wacker.com](http://www.wacker.com)

**Further Information:**

Product data sheets and material safety data sheets of WACKER® - products can be ordered from our WACKER- subsidiaries or via the Internet [www.wacker.com](http://www.wacker.com).

For further questions, please contact our WACKER® SILICONES INFO-SERVICE:

Wacker Chemie AG  
WACKER SILICONES  
Hanns-Seidel-Platz 4  
D-81737 München

e-mail: [info.silicones@wacker.com](mailto:info.silicones@wacker.com)  
phone: +49 89 6279-0

WACKER® is a registered trademark of Wacker Chemie AG.

The data presented in this starting formulation are in accordance with the present state of our knowledge. The information given in this starting formulation should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the product for a particular purpose.