

CAR CARE**Rinse Off Agent AWK 14**

Properties: Rinse off agent AWK 14 is used in automatic car washes. It is sprayed on after the car has been washed and effects a fast breakdown of the water film. Thus, remaining water can be easily removed by blowers.
Application ratio: 1 : 5000 to 1 : 50000.

Ingredient	Weight [%]	Description
1 WACKER® L 656	42.0	Silicone fluid
2 Exxsol D 100 S	10.0	Hydrocarbons free from aromatics
3 Isopropyl alcohol	10.0	
4 Acetic acid conc.	3.4	
5 Genamin® CTAC	20.0	Hexadecyltrimethylammonium chloride
6 Genapol® X 080	10.0	Alkoxyated alcohol
7 Water	4.6	

Procedure: Mix the ingredients in the order given at room temperature.

Suppliers:	1	Wacker Chemie AG	www.wacker.com
	2	ExxonMobil Corporation	www.exxonmobilchemical.com
	3, 4	VWR International GmbH	www.vwr.com
	5, 6	Clariant GmbH	www.clariant.com

Further Information:

Product data sheets and material safety data sheets of WACKER® - products can be ordered from our WACKER- subsidiaries or via the Internet www.wacker.com.

For further questions, please contact our WACKER® SILICONES INFO-SERVICE:

Wacker Chemie AG
WACKER SILICONES
Hanns-Seidel-Platz 4
D-81737 München

e-mail: info.silicones@wacker.com
phone: +49 89 6279-0

WACKER® is a registered trademark of Wacker Chemie AG.

The data presented in this starting formulation are in accordance with the present state of our knowledge. The information given in this starting formulation should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the product for a particular purpose.