

WACKER

CREATING TOMORROW'S SOLUTIONS

VINNAPAS®

PRIMIS®



ARCHITECTURAL COATINGS | POLYMER DISPERSIONS | AUSTRALIA /
NEW ZEALAND

PRODUCT OVERVIEW

POLYMER CHEMISTRY – A KEY TO QUALITY

Polymer binders enhance two critical characteristics of all mortars and coatings: adhesion and flexibility. They ensure the quality of buildings and prolong their life expectancy while reducing material consumption. At the same time, they increase creative freedom by making it possible to combine a wide variety of construction materials.


Vinyl Acetate-Ethylene (VAE) – Serving the Megatrends of Today and Tomorrow

VINNAPAS® dispersions are co- and terpolymers based on vinyl acetate, ethylene and other monomers. Vinyl acetate-ethylene (VAE), in particular, combines technical performance with environmental benefits at an attractive cost-in-use ratio.

VAE dispersions are produced by the emulsion polymerization of the hard, polar monomer vinyl acetate and the soft, hydrophobic monomer ethylene. Ethylene functions as an optimal flexibilizer for vinyl acetate, incorporating permanent flexibility into VAE polymers. Consequently, the use of plasticizers can be minimized when formulating with VAEs. In addition, all grades are stabilized without the use of APEO-based surfactants, many of them also show low residual monomer content (<500 ppm).

Compliance with Strict Labels

With our cutting-edge VINNAPAS® VAE binders, the construction and paint industries are equipped to meet stringent governmental regulations, as well as the requirements of internationally recognized ecolabels and certifications, such as Blue Angel, Green Seal GS-11, TÜV Süd and EMICODE EC1 plus.



THE FAST TRACK – PRODUCT FINDER

Grade	Typical General Properties ¹							
	Polymer Base ²	Solids Content ±1% ³ [%]	Viscosity, Brookfield [mPa·s]	pH Value	Glass Transition Temperature T _g (DSC) ⁵ [°C]	Minimum Film-Forming Temperature [°C] (ISO 2115) ⁵	Predominant Particle Size ⁵ [µm]	Stabilization System ⁴
VINNAPAS® EF 818	VAc-E	55	150–650	4.0–6.0	7	0	0.22	ST
VINNAPAS® EP 3360 (ULS)	VAc-E	60	3,000–6,000	4.0–6.0	10	2	0.3	PVOH & ST
VINNAPAS® EZ 3067	VAc-E	55	2,000–7,000	4.5–5.5	6	1	0.4	CD & ST
VINNAPAS® CEZ 3031	VAc-E-VC	50	6,000–12,000	4.0–5.0	7	2	0.7	CD & ST
VINNAPAS® EZ 3112	VAc-E-VE	50	1,800–4,000	4.5–5.5	9	0	0.4	CD & ST
PRIMIS® AF 1000	A	42	70–150	8.0–9.0	20	9	<0.1	ST
PRIMIS® SAF 9000	S-A	42	50–500	6.5–7.5	21	13	<0.1	ST

¹ These figures are only intended as a guide and are not part of supply specifications.

² VAc = vinyl acetate

A = acrylate

E = ethylene

S = styrene

VC = vinyl chloride

VE = VERSA® vinyl ester

³ Residue after drying

⁴ PVOH = polyvinyl alcohol

CD = cellulose derivative

ST = surfactant

⁵ Approximately

THE PERFECT FIT – RECOMMENDATION BY APPLICATION

Grade	Recommended Applications								
	Interior Paints			Easy-to-Clean Paints	Exterior Paints			Intumescent & Fire-Resistant Paints	
	Low PVC	Medium PVC	High PVC		Masonry Paints	Textured Paints	Elastomeric/ Crack-Bridging Paints	Intumescent Paints	Fire-Resistant Paints
VINNAPAS® EF 818	○	○							
VINNAPAS® EP 3360 (ULS)		●	●						
VINNAPAS® EZ 3067							●		
VINNAPAS® CEZ 3031	●	○		●	●	●		●	
VINNAPAS® EZ 3112							●		
PRIMIS® AF 1000				●	●				
PRIMIS® SAF 9000				●					

● Highly recommended

○ Recommended

Interior Paints

Grade	Product Benefit	Performance Attributes			
		Scrub Resistance	Gloss Development	Block Resistance	Compatibility with Tinting Systems
VINNAPAS® EP 3360 (ULS)	Excellent scrub resistance and high solids content, supports modern manufacturing processes.	●			●
VINNAPAS® EF 818	Standard binder with excellent abrasive scrub resistance.	○	○	○	●
VINNAPAS® CEZ 3031	Premium binder for interior and exterior paints with good fire-resistant properties.	○	○		●

Easy-to-Clean Paints

Grade	Product Benefit	Performance Attributes		
		Stain Resistance	Resistance to Dirt Pick-Up	Compatibility with Other Binders
PRIMIS® SAF 9000	High-performance additive used as a co-binder to increase stain resistance and easy-to-clean properties of interior paints. Compatible with a broad range of main binders.	●	●	●

Exterior Paints

Grade	Product Benefit	Performance Attributes						
		Resistance to Dirt Pick-Up	Hydrophobicity/Water Resistance	Flexibility	Color Stability	Saponification/Alkaline Resistance	Flame Resistance	Durability
PRIMIS® AF 1000	State-of-the-art exterior binder with very low dirt pick-up and very high color stability.	●	●	●	●	●	○	●
VINNAPAS® CEZ 3031	Broad utility binder with excellent color stability.	○	○	●	●	●	●	●
PRIMIS® SAF 9000	High-performance additive used as a co-binder to reduce snail trails and leeching of water-soluble additives in general. Compatible with a broad range of main binders.	●	●	N.A.	N.A.	N.A.	N.A.	N.A.

● Excellent ○ Good

Intumescent Coatings

Grade	Product Benefit	Performance Attributes				
		Foam Development	Foam Stability/ Integrity	Paint Storage Stability under Demanding Conditions	Broad Formulation Ability	Dry Film Thickness (DFT) Efficiency
VINNAPAS® EZ 3112	Premium binder that provides maximum performance for a very wide range of applications.	●	●	●	●	●
VINNAPAS® EZ 3067	Standard binder for high-performance intumescent coatings.	○	●	○	○	○

Fire-Resistant Paints

Grade	Product Benefit	Performance Attributes		
		Flame Retardancy	Hydrophobicity	Flexibility
VINNAPAS® CEZ 3031	General-purpose binder with good fire-resistant properties.	○	○	●

● Excellent ○ Good

WACKER

Wacker Chemicals Australia Pty. Ltd

1/35 Dunlop Road
Mulgrave Vic 3170, Australia
Tel. +61 3 9541 8900
info.australia@wacker.com

www.wacker.com
www.wacker.com/move

www.wacker.com/socialmedia



The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.