


BELSIL® SDM 5055 VP



Silicone Fluids, functional (INCI)

BELSIL® SDM 5055 VP is a silicone wax. In accordance with CTFA, it is classified as Stearyl Dimethicone. This product displays good compatibility with many cosmetic raw materials including oils, waxes, fatty alcohols and fatty acids.

INCI Stearyl Dimethicone



Technical data

General Characteristics

Property	Condition	Value	Method
Appearance	-	white, opaque solid	-
Density	50 °C	approx. 0.86 g/cm ³	not specified
Flash point	-	160 °C	ISO 2592
INCI name	-	Stearyl Dimethicone	-
Melting point	1013 hPa	approx. 30 °C	Lit.
Viscosity, dynamic	50 °C	approx. 400 mPa·s	Brookfield

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

Applications

- Conditioners
- Eye Make-up
- Hair Styling
- Lip Make-up
- Make-up Foundation
- Skin Care
- Sun Care

Application details

The main fields of application of this alkyl-functional silicone is Skin Protection, Skin Care and Color Cosmetics. In creams and lotions it improves the efficacy of the formulation and confers a non-sticky, soft skin feel. Due to its high substantivity, enhanced water resistance, and moisturizing benefits, alkylfunctional silicones prove to be advantageous components in Colour Cosmetics, such as Lipstick, Mascara, and Foundation.

Packaging and storage

Storage

The "Best use before end" date of each batch is shown on the product label.

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site <http://www.wacker.com>.

QR Code BELSIL® SDM 5055 VP



For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Gisela-Stein-Strasse 1, 81671 Munich, Germany
productinformation@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.