

PULPSIL[®] 959 S

Silicone Fluid Emulsions, functional

PULPSIL[®] 959 S is an aqueous solution of a hydrolytically stable, polyethermodified silicone fluid.

Properties

PULPSIL[®] 959 S is characterized by:

- improved cleaning properties towards conventional mechanical cleaning
- increase of processing speed
- low surface tension
- good wetting properties
- easy processing
- good solubility in water

Technical data

General Characteristics

Property	Condition	Value	Method
Ionogenity	-	nonionic	-
Solid Content	-	approx. 10 %	Microwave oven
Solubility in water	completely miscible	-	-
Viscosity, dynamic	25 °C Brookfield, spindle 1 / 50 rpm	approx. 10 mPa-s	Brookfield
pH	-	approx. 5	Indicator strips

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

Applications

- Antifoams for Textile Finishing
- Chemical Industry
- Pulp Solutions
- Pulp, Paper & Printing Processes

Application details

PULPSIL® 959 S is a solution used for cleaning and finishing of the drying canvas of a pulp-/paper-/cardboard-/tissue machine and is usually applied by spraying. Due to the diversity of PULPSIL® 959 S also other application areas than in the pulp- and paperprocess are also possible.

PULPSIL® 959 S can be easily diluted with water. We recommend starting with PULPSIL® 959 S and then adding water while stirring continuously.

Packaging and storage

Storage

The ‚Best use before end‘ date of each batch is shown on the product label.

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site (<http://www.wacker.com>).

QR Code PULPSIL® 959 S



For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Hanns-Seidel-Platz 4, 81737 Munich, Germany
info@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.