

# **ADVALON® CI 40**



## Silicone Fluid Emulsions

ADVALON® CI 40 is a nonionic semi-micro emulsion of a reactive polysiloxane. It is a fabric softener designed especially for polyester to impart a good hand together with a substantial intensification of dark color shades.

# **Properties**

ADVALON® CI 40 gives a pleasant, supple hand to polyester fabrics. Most importantly, ADVALON® CI 40 significantly deepens the color of disperse dyed polyester without promoting the thermomigration of the dyes. Therefore it enables deeper color shades and noticeable savings of dyestuff.

## Specific features

- Emulsions
- · Low viscosity

## Technical data

### **General Characteristics**

Property	Condition	Value	Method
рH	-	approx. 5	Indicator strips
Solid content	-	approx. 35 %	Microwave oven
Appearance	-	brownish, translucent	-
lonogenity	-	nonionic	-

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

# **Applications**

- Textile & Leather
- Textile Color Enhancement
- Textile Finishing

## **Application details**

## Application:

ADVALON® CI 40 is recommended for padding application on polyester under common conditions. It can be used on its own or together with organic fabric softeners and other finishing agents. The individual compatibility should be tested on a case-by-case basis.

### Processing:

For optimum finishing results ADVALON $^{\circ}$  CI 40 should be applied by padding at bath concentrations around 50 g/l. Liquor pickup 70 – 80 %. The silicone finish will cure quickly upon heat drying of the fabric. Stenter curing at 120  $^{\circ}$ C is recommended.

# Packaging and storage

# **Packaging**

- 0,5 kg bottle
- 200 kg drum
- 950 kg IBC

## **Storage**

The 'Best use before end' date of each batch is shown on the product label. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

# Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site http://www.wacker.com.

# QR Code ADVALON® CI 40



## For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Hanns-Seidel-Platz 4, 81737 Munich, Germany productinformation@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.