

# E35 60000

## Silicone Fluid Emulsions

Silicone Emulsion E35 60000 is a 35% emulsion of a high viscosity Polydimethylsiloxane. It is designed to be used in many applications, such as mold release, car and furniture polish, and other specialty product applications. The E35 Series emulsions contain sodium nitrite as a corrosion inhibitor. These emulsions should not be used in contact with amines.

### Properties

- Ease and versatility of application
- Chemical inertness

### Technical data

#### General Characteristics

Property	Condition	Value	Method
Emulsifier type	-	Nonionic	-
Appearance	-	White	-
Dilution <sup>(1)</sup>	200 ppm   30 d	2 %	-
Solid content	-	38 %	-

<sup>1</sup>No separation

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

## Applications

- Chemical Industry

## Application details

In mold release applications, Wacker's silicone emulsions are normally diluted to 0.5% - 2.5%. However, in a polish or specialty product formulation, the emulsions are normally used in their concentrated form. Optimum performance is often achieved by blending E35 60000 with another E35 series emulsion, for a combination of properties. Normally, a higher viscosity silicone gives good durability and gloss, while the lower viscosity is easier to apply and rub out.

## Packaging and storage

### Storage

Under normal warehouse conditions, these emulsions are stable in unopened containers for 12 months. Freezing should be avoided and these emulsions should not be stored above 32°C (90°F). The "Best use before end date" of each batch is shown on the Certificate of Analysis. Storage beyond the date specified on the Certificate of Analysis does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

## Safety notes

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet.

## QR Code E35 60000



### For technical, quality or product safety questions, please contact:

**Wacker Chemie AG**, Hanns-Seidel-Platz 4, 81737 Munich, Germany  
info@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.