

# Silfoam<sup>®</sup> SE 1220

## Silicone Antifoam Emulsions

Silfoam<sup>®</sup> SE 1220 is a 10% active, low viscosity defoamer emulsion that is designed for controlling foam in aqueous systems.

Silfoam<sup>®</sup> SE 1220 is safe to be used in alkaline and high temperature applications. It provides excellent foam knockdown as well as prevents foam reoccurrence longer than most conventional defoamers.

Silfoam<sup>®</sup> SE 1220 is certified as Kosher. It is suitable for use in indirect food contact and secondary direct food additive applications listed under FDA 21 CFR 176.170; 176.180; 176.200; 176.210; 175.300, 177.2600; 178.3400; and 173.340. Some of the listed applications have regulatory limitations, please contact your Wacker Sales Representative for further information.

## Technical data

### General Characteristics

Property	Condition	Value	Method
Appearance	-	Milky-White Liquid	WSTM 3043
Active content	-	10 %	-
Dosage up-limit if used as secondary direct food additive applications	-	100 ppm	-
Ionic character	-	Nonionic	-
Viscosity, dynamic	25 °C	approx. 700 mPa·s	WSTM 3342

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

## Application details

Silfoam® SE 1220 is a versatile defoamer that is suitable to be used in many food or industrial applications, especially for food washing and processing, beverage, and alcohol distillation processes.

Silfoam® SE 1220 is easily dispersible in water. It is usually applied straight to an aqueous foaming system to control the foam.

Prior to use, Silfoam® SE 1220 should be gently stirred with minimum shear to assure uniformity of the emulsion.

## Packaging and storage

### Storage

The "Best use before end date" of each batch is shown on the Certificate of Analysis. Storage beyond the date specified on the Certificate of Analysis does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

## Safety notes

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet.

## QR Code Silfoam® SE 1220



### For technical, quality or product safety questions, please contact:

**Wacker Chemie AG**, Hanns-Seidel-Platz 4, 81737 Munich, Germany  
productinformation@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.