

WACKER[®] L 656

Functional Silicone Fluids

WACKER[®] L 656 is an aminoalkyl functional polydimethylsiloxane. In comparison with other curable amino silicone fluids, WACKER[®] L 656 exhibits an increased storage stability both as 100 % fluid and in ready-to-use formulations.

Technical data

General Characteristics

Property	Condition	Value	Method
Viscosity, kinematic	25 °C	15 - 35 mm ² /s	DIN 51562-1
Refractive index	25 °C	1.4090 - 1.4120	DIN 51423
Amine number	-	1.20 - 1.40 meq/g	-
Appearance	-	clear	-

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

Applications

- Rinse-Off Agents
- Paint Conditioners
- Water-Repellent Agents for Glass

- Paint Polishes
- Wash-and-Wax Agents
- Polyurethane Processing
- Paint & Plastic Polishes

Application details

WACKER® L 656 can be used as a component for rinse-off agents in automatic car washes. For these formulations, WACKER® L 656 is converted into its cationic form by neutralization with organic acids and, thus, shows an enhanced affinity to car bodies. In combination with cationic emulsifiers and tensides, protonated WACKER® L 656 improves the break-down and sheeting of the water film as well as conditioning effects and gloss level. WACKER® L 656 can be applied frequently without formation of any build-up.

WACKER® L 656 is used in paint conditioners and paint polishes in order to provide superior gloss and detergent resistance. In comparison with conventional polydimethylsiloxanes of the series WACKER® AK, aminoalkyl functional WACKER® L 656 exhibits an excellent affinity to various substrates. Gloss and depth of color are retained for a longer period of time.

Packaging and storage

Storage

The 'Best use before end' date of each batch is shown on the product label. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site <http://www.wacker.com>.

QR Code WACKER® L 656



For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Hanns-Seidel-Platz 4, 81737 Munich, Germany
info@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.