

SILFOAM[®] SE 1060



Silicone Antifoam Emulsions

SILFOAM[®] SE 1060 is a versatile antifoam emulsion, which contains a comparatively high amount of emulsifier. It features a high resistance to alkalis and acids and may further be used in a wide range of areas in which pH is critical.

Properties

SILFOAM[®] SE 1060 has proved ideal for tackling foam in surfactant rich formulations. It is mainly used in wastewater treatment but it is also a useful auxiliary in many processes of the chemical industry.

Technical data

General Characteristics

Property	Condition	Value	Method
Appearance	-	milky, white	-
Density	20 °C	approx. 1 g/cm ³	DIN 51757
Diluent	-	water	-
Emulsifier type	-	o/w, nonionic	-
Solid content	-	approx. 11 %	Microwave oven
Viscosity, dynamic	25 °C	approx. 50 mPa·s	-
pH	25 °C	approx. 6	Indicator strips

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

Applications

- Antifoams

Application details

SILFOAM® SE 1060 is a low-viscosity emulsion, it can be metered readily, with stable dispersions easily attainable in high-viscosity formulations.

In low-viscosity products, preliminary compatibility and stability tests should be performed on the system to be defoamed. The amount to add to liquid formulations depends on the desired degree of foam control, but usually lies between 0.1 and 2 %.

If SILFOAM® SE 1060 is to be added during a process, the emulsion should be added undiluted, as it is already sufficiently dispersed by its emulsion form.

Especially after a longer storage time we recommend to stir the emulsion before use (approx. 3 minutes with a propeller stirrer at 200 – 400 rpm).

But be cautious: too high shear can break the emulsion.

If feed pumps are used, they should be of the low shear force type.

Packaging and storage

Storage

Minimum temperature allowed during storage and transportation:

0 °C

Maximum temperature allowed during storage and transportation:

40 °C

The 'Best use before end' date of each batch is shown on the product label. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site <http://www.wacker.com>.

QR Code SILFOAM® SE 1060



For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Hanns-Seidel-Platz 4, 81737 Munich, Germany
info@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.